

# PROFESSIONAL CONDENSATION DEHUMIDIFIERS CONSTRUCTION



- ▼ Long-lasting steel casing
- ▼ High efficiency
- ▼ Hour counter
- ▼ Large water tank with automatic shut-off when full
- ▼ Possibility of continuous operation (24 h/day)
- ▼ Possibility to connect a hose to remove condensed water
- ▼ Tank full indicator
- ▼ Air filter
- ▼ Automatic fast defrosting by hot gases
- ▼ Restarts automatically after a power failure
- ▼ Large wheels and handle
- ▼ Built-in hygrostat



Wide spaces between evaporator tubes prevent clogging.



Compact foam air filter enables work in very dusty spaces.



Manual control resistant to harsh conditions.

## SPECIFICATIONS

## DH 62

Capacity (30°C/80% RH)	l/24h	52
Capacity (20°C/60% RH)	l/24h	20
For rooms of approx.	m <sup>3</sup>	780
For restoration after flooding	m <sup>3</sup>	312
Air displacement	m <sup>3</sup> /h	480
Operating range: temperature	°C	1-42
humidity	%	30-70
Refrigerant		R1234YF
Power consumption	W	860
Power supply	V	220-240
Frequency	Hz	50
Noise	dB(A)	53
Compressor		rotary
Tank capacity	l	12
Product size (l x w x h)	mm	600 x 580 x 850
Box size (l x w x h)	mm	590 x 580 x 850
Net/gross weight	kg	47/51
Pallet	pcs	4
Dual voltage		available no